



Instructions

Installs in seconds with
no tools required!

Installation

- Twist the cooler off the mounting bracket.
- Remove the wingnut from the bolt and remove the bolt from the bracket.
- Add or remove rubber gaskets as required to fit your shaft.
- Locate the Cool Caddy on your pull cart shaft near the golf bag but not close enough to obstruct the cooler from swivelling.
- Feed the bolt through the square hole in the bracket, through the gaskets holes and out the round hole.
- Put the wing nut on the threaded bolt end and twist until snug.
- Attach the cooler and check the range of motion.
- Re-locate bracket as required and tighten bolt.



**TWIST cooler OFF
to remove**




Usage

- Remove hot cup for 12 oz. cans.
- Twist cans to remove from cooler.
- Remove cans immediately after use.
- Tighten wingnut as necessary.
- Keep the Velcro surfaces free of debris.
- Store cooler in golf bag when not in use.



**Push ON & DOWN
FIRMLY to attach**



The cooler **MUST** be **PUSHED ON** and **DOWN FIRMLY** to attach it correctly to the mounting plate. If you do not attach the cooler properly it may fall off during use. Remove cans by **TWISTING** them out **NOT PULLING**. The coolers are made of soft foam and will rip if pulled hard enough.

US Patent No. 5,494,284
Can. Patent No. 2,149,980

www.coolcaddy.com

Cool Caddy Inc. 200-32 Balmoral St. Winnipeg, Manitoba R3C 1X4 Toll Free: 1-866-477-9550